

CARBONWEB® VMP-AG V-BANK MINI-PLEAT

RENSA

CarbonWeb® VMP-AG V-Bank Mini-Pleat is an exceptionally high-quality industrial grade HVAC molecular air filter specifically designed to remove a broad spectrum of soft and hard acid gasses such as sulfur dioxide, hydrogen sulfide, hydrochloric acid and acetic acid. The VMP-AG also targets nitrogen oxides, NOx, NO₂ & NO₃.

翻

VMP-AG is constructed with a heavy 640 gsm weight media of 100% potassium base impregnated carbon 30x60 fine mesh granules. The extended surface mini-pleat V-bank design optimizes dwell time for adsorption while reducing resistance to air flow. Reducing energy costs and maximizing service life.



HVAC applications typically experience lower concentration levels of corrosive gasses. Adsorption is an effective and economical process to mitigate soft and hard gas issues. Heavy weight media and fine mesh carbon provide excellent first pass efficiencies. When properly applied the CarbonWeb VMP-AG can mitigate or eliminate problems caused by unwanted destructive acid-gasses and vapors found in HVAC systems and climate-controlled spaces.

CARBONWEB VMP-AG

is constructed with heavy weight potassium base impregnated carbon designed to remove or mitigate corrosive acid-gasses.

- Museums Art & Archive
- Preservation
- Corrosion Control for Electronic Drives
- Corrosion Control for Computers
- Pulp and Paper Mills
- Wastewater Treatment
- Petrochemical
- Microelectronics Manufacturing

Model	Nominal Size	High Activity carbon	Weight Each	Initial Resistance WC	Initial MERV	Final Resistance WG
CarbonWeb VMP-AG				500 FPM		
VMPAG-12-100-01	12x24x12	640 gsm	8.9 LBS	0.23"	8	1.5"
VMPAG-12-100-06	20x24x12	640 gsm	13.0 LBS	0.23"	8	1.5"
VMPAG-12-100-08	24x24x12	640 gsm	15.5 LBS	0.23"	8	1.5"

PERFORMANCE DATA

= N S



SPECIFICATIONS

- **Media:** 640 gsm 100% potassium based high activity 30x60 fine-mesh impregnated carbon suspended in a non-woven matrix.
- **Frame:** Double walled high strength plastic V-design frame for industrial applications with minimum resistance to air flow.
- **Sealant:** Media pack shall be bonded to frame utilizing moisture resistant adhesive for continuous seal.
- **Gasketing:** Optional premium closed cell neoprene gasketing available.
- Maximum Operating Temp: 140F.
- Incinerable: Yes

INDUSTRIAL GRADE PLASTIC FRAME

with Double Wall Construction





ENGINEERED DESIGN

Filter Strength with

Maximizes Air-Flow and



PRECISION PLEATING

for Optimum Surface

Area and Increased

Dwell Time



For questions and orders contact Rensa Filtration at **info@rensafiltration.com** or visit **rensafiltration.com**

D-Mark

130 N. Groesbeck Highway Mt. Clemens, MI 48043 800-343-3610 | www.dmarkinc.com